

Vital patient data at a glance



Sentec Connectivity enables the transmission of oxygenation and ventilation monitoring – **tcPCO₂, tcPO₂, SpO₂, Pulse Rate (PR), Heating Power (HP)** – to GE patient monitors via the Unity Network ID.



Sentec Connectivity

GE Healthcare patient monitor series via Unity Network™ ID

- Sentec Digital Monitor readings and alarms are duplicated on GE patient monitors
- The Sentec Digital Monitor is automatically identified when connected to a GE Unity Network ID through a dedicated device identification communication adapter (DIDCA)
- Cost-effective patient data monitoring for clinicians

Care with
Confidence

Sentec Connectivity

GE Healthcare patient monitor series via Unity Network™ ID

Required Components	System Requirements	Description
Sentec Digital Monitor (SDM) 	Software version V08.00 to V08.03	Provides noninvasive and continuous real-time monitoring of ventilation and oxygenation
GE Healthcare patient monitors 	V 2 V 1 V 4A V 4E V 3A	Carescape B450 Carescape B650 / B850 Solar 8000 M Solar 8000 I Dash 5000
Unity Network ID 	Version 8 or higher	Transmits tcPCO ₂ , tcPO ₂ , SpO ₂ , Pulse Rate (PR) and Heating Power (HP) from SDM to GE patient monitors
Device Identification Communication Adapter (DIDCA) 	Version v1.5.2 or higher	One adapter to connect SDM with standard LAN cable
Standard LAN cable (RJ45) 		Connection between DIDCA and GE Unity Network ID

Sentec Connectivity Support Team

Let's connect.

If you need support, please contact your local Sentec representative, send an e-mail to connectivity@sentec.com or consult your GE Healthcare representative.

Please visit www.sentec.com for more information.

Your local distributor:



Ringstrasse 39
4106 Therwil
Switzerland
www.sentec.com
 Made in Switzerland

Sentec Connectivity Support Team:
Tel +41 61 726 97 60
connectivity@sentec.com

Note: This is a global overview and may contain information on products not released in all markets/countries. Information is subject to change without notice.